


The Best Products, The Best Service...

SERVICE METAL

ONE CALL GETS IT ALL



Hex Bushing 150# Malleable Iron Inches / Pounds



Size	A	B	Approximate Weight (in Pounds)	Hex
1/4 x 1/8	0.61	0.66	0.03	Out
3/8 x 1/8	0.81	0.73	0.05	Out
3/8 x 1/4	0.81	0.73	0.04	Out
1/2 x 1/8	0.95	0.88	0.09	Out
1/2 x 1/4	0.95	0.88	0.08	Out
1/2 x 3/8	0.95	0.88	0.07	Out
3/4 x 1/8	0.95	1.18	0.14	Out
3/4 x 1/4	1.05	1.18	0.15	Out
3/4 x 3/8	1.05	1.18	0.14	Out
3/4 x 1/2	1.05	1.18	0.12	Out
1 x 1/8	1.12	1.15	0.19	In
1 x 1/4	1.12	1.15	0.19	In
1 x 3/8	1.16	1.15	0.23	In
1 x 1/2	1.16	1.40	0.22	Out
1 x 3/4	1.18	1.40	0.18	Out
1 1/4 x 1/8	1.16	1.15	0.32	In
1 1/4 x 1/4	1.16	1.15	0.27	In
1 1/4 x 3/8	1.20	1.15	0.25	In
1 1/4 x 1/2	1.25	1.38	0.34	In
1 1/4 x 3/4	1.25	1.80	0.38	Out
1 1/4 x 1	1.25	1.80	0.30	Out
1 1/2 x 1/8	1.30	1.18	0.45	In
1 1/2 x 1/4	1.30	1.18	0.38	In
1 1/2 x 3/8	1.30	1.18	0.39	In
1 1/2 x 1/2	1.30	1.40	0.42	In
1 1/2 x 3/4	1.30	1.66	0.45	In
1 1/2 x 1	1.30	1.95	0.47	Out
1 1/2 x 1 1/4	1.30	1.95	0.31	Out
2 x 1/4	1.40	1.18	0.64	In
2 x 3/8	1.40	1.18	0.63	In
2 x 1/2	1.50	1.37	0.55	In

The Best Products, The Best Service...

SERVICE METAL

ONE CALL GETS IT ALL



Size	A	B	Approximate Weight (in Pounds)	Hex
2 x 3/4	1.50	1.68	0.60	In
2 x 1	1.50	1.97	0.65	In
2 x 1 1/4	1.50	2.55	0.81	Out
2 x 1 1/2	1.50	2.55	0.66	Out
2 1/2 x 1/2	1.70	3.25	1.60	Out
2 1/2 x 3/4	1.58	1.65	0.82	In
2 1/2 x 1	1.58	2.00	0.90	In
2 1/2 x 1 1/4	1.58	2.40	1.00	In
2 1/2 x 1 1/2	1.58	2.70	1.06	In
2 1/2 x 2	1.65	3.00	0.98	Out
3 x 1/2	1.88	3.80	2.10	Out
3 x 3/4	1.75	1.70	1.48	In
3 x 1	1.70	2.00	1.44	In
3 x 1 1/4	1.70	2.40	1.40	In
3 x 1 1/2	1.70	2.70	1.44	In
3 x 2	1.80	3.70	2.20	Out
3 x 2 1/2	1.90	3.90	1.82	Out
3 1/2 x 1 1/2	1.75	2.75	2.10	In
3 1/2 x 2	1.94	1.80	2.16	In
3 1/2 x 2 1/2	1.70	4.30	2.50	Out
3 1/2 x 3	1.75	4.60	2.10	Out
4 x 1/2	2.00	4.80	4.30	Out
4 x 3/4	2.00	2.00	2.30	In
4 x 1	1.90	2.00	2.34	In
4 x 1 1/4	1.90	2.40	2.24	In
4 x 1 1/2	1.90	2.70	2.10	In
4 x 2	1.90	3.30	2.74	In
4 x 2 1/2	2.10	4.70	3.84	In
4 x 3	2.10	4.70	3.20	Out
4 x 3 1/2	2.33	4.75	2.92	Out
5 x 2	2.05	3.30	4.26	In
5 x 2 1/2	2.10	4.00	4.55	In
5 x 3	2.10	4.70	4.95	In
5 x 4	2.10	5.80	4.36	Out
6 x 1 1/2	2.20	3.35	6.74	In
6 x 2	2.20	3.35	6.00	In
6 x 2 1/2	2.20	3.90	6.58	In
6 x 3	2.30	4.70	6.32	In
6 x 4	2.30	5.90	6.78	In
6 x 5	2.50	7.20	7.28	Out

The Best Products, The Best Service...

SERVICE METAL

ONE CALL GETS IT ALL



Size	A	B	Approximate Weight (in Pounds)	Hex
8 x 6	2.75	9.00	16.40	Out

**Malleable Castings conform to ASTM A197*

**Hot-Dipped Galvanized Fittings conform to ASTM A153*

**Malleable Fitting Dimensions conform to ASME B16.3*

**Malleable Bushings, Plugs and Locknuts conform to ASME B16.14*

**Malleable Unions conform to ASME B16.39*

**NPT Threads on all fittings conform to ASME B1.20.1*

**Class 150 fittings are UL listed and FM approved at 300 psi*

**Class 300 fittings are UL listed*