


The Best Products, The Best Service...

SERVICE METAL

ONE CALL GETS IT ALL



Square Head Plug, Cored
150# Malleable Iron
Inches / Pounds



| Size | A | Approximate Weight (in Pounds) |
|-------|------|--------------------------------|
| 1/8 | 0.65 | 0.02 |
| 1/4 | 0.75 | 0.03 |
| 3/8 | 0.85 | 0.05 |
| 1/2 | 1.00 | 0.09 |
| 3/4 | 1.15 | 0.14 |
| 1 | 1.30 | 0.22 |
| 1 1/4 | 1.40 | 0.37 |
| 1 1/2 | 1.50 | 0.54 |
| 2 | 1.60 | 0.82 |
| 2 1/2 | 1.85 | 1.30 |
| 3 | 1.95 | 1.70 |
| 3 1/2 | 2.10 | 2.50 |
| 4 | 2.30 | 2.62 |
| 5 | 2.50 | 5.26 |
| 6 | 2.80 | 6.58 |

**Malleable Castings conform to ASTM A197*

**Hot-Dipped Galvanized Fittings conform to ASTM A153*

**Malleable Fitting Dimensions conform to ASME B16.3*

**Malleable Bushings, Plugs and Locknuts conform to ASME B16.14*

**Malleable Unions conform to ASME B16.39*

**NPT Threads on all fittings conform to ASME B1.20.1*

**Class 150 fittings are UL listed and FM approved at 300 psi*

**Class 300 fittings are UL listed*