


NO	DESCRIPTION	MATERIAL	Q'TY	STANDARD	REMARKS
1	Retainer Plate	SS41	1	JIS G 3101	Galvanized
2	Retainer Plate Screw	SS41	2	JIS G 3101	Galvanized
3	Packing	EPDM	1	MAKER	
4	Body	CAST IRON / EN-GJL-250 DUCTILE IRON / GG-40	1	ASTM A126 / EN 1561 ASTM A536 / DIN 1693	
5	Seat	EPDM NBR SILICON VITON	1	MAKER MAKER MAKER MAKER	
6	Disc	DUCTILE IRON / GG-40	1	ASTM A536 / DIN 1693	Galvanized
		CF8	1	ASTM A351	
		CF8M	1	ASTM A351	
		ALUMINIUM BRONZE	1	JIS H 5114 ALBC2	
7	Upper Stem	SUS304	1	ASTM A276	
		SUS316	1	ASTM A276	
		SUS304	1	ASTM A276	
8	Lower Stem	SUS304	1	ASTM A276	
		SUS316	1	ASTM A276	
9	Plug	SS41	1	JIS G 3101	

NOTE :

1. BASIC DESIGN : BS5155, IS05752  
AP1609, MS-SP67
2. TOP FLANGE : IS05211
3. HYDRO. TEST  
BODY : 24 Bar  
SEAT : 17.6 Bar



EMBOSSING	
FRONT	BACK
<b>ST</b>	SIZE
MATERIAL	PRESSURE

Size 10" ~ 12"

<b>STONETOWN CORP.</b>				DATE	05.08.22	NAME	MODEL	STL
				SCALE	NONE			
APP.BY	CHK.BY	DRG.BY	REV.NO	LUGGED TYPE PINLESS BUTTERFLY VALVE (MATERIAL TABLE)		DRG.NO	V-B-LG-00M	
			5				- 1/2	